

# LOCTITE®

## QUICKSTIX™

Get the job done right

Getting the job done right means having the right tools in hand.

Make sure that you have Loctite® QuickStix™ in your toolbox to get the job done right the first time and on time.

NEW Loctite® QuickStix™ Holster is designed to hook onto your toolbox and toolbelt for easy portability of Loctite® QuickStix™

### KEY BENEFITS OF LOCTITE® QUICKSTIX™

- Keep toolboxes, workbenches, and hands clean
- Convenient: small enough to be “pocket friendly”
- Great for overhead use: no drips, leaks, or spills
- Fast and easy to apply
- Color-coded caps for easy application identification



LOCK



SEAL



GASKET



RETAIN



PROTECT



ACCELERATE

**MIX AND MATCH ANY 5 LOCTITE® QUICKSTIX™ TO MEET YOUR MAINTENANCE AND REPAIR NEEDS AND RECEIVE FREE HOLSTER! PLACE YOUR ORDER TODAY!**



Henkel



Essential tools for any toolbox, bag or belt.

Semisolid formulas allow for easy portability of Loctite® QuickStix™, the same trusted performance as Loctite® liquid threadlocker, thread sealant, retaining, gasketing, and anti-seize products.



THREADLOCKING

THREAD SEALING

GASKETING

RETAINING

ANTI-SEIZE

PRIMER

**Loctite® QuickStix™ 248™ Threadlocker – Medium Strength**  
Medium strength threadlocker eliminates loosening from vibration, shock, and thermal expansion.

**Loctite® QuickStix™ 268™ Threadlocker – High Strength**  
High strength threadlocker eliminates loosening from vibration, shock, and thermal expansion.

**Loctite® QuickStix™ 561™ PST® Pipe Sealant**  
Instant low pressure seal to 100 psi. Prevents galling; protects from rust and corrosion. Chemically resistant.

**Loctite® QuickStix™ 548™ Gasket Eliminator® Flange Sealant**  
Rigid flange sealant forms a flexible, solvent-resistant seal. Excellent oil resistance. Operates to 300°F.

**Loctite® QuickStix™ 534™ Hi-Tack Gasket Dressing**  
Holds pre-cut gaskets in place for assembly and allows repositioning. Easy to use. Seals to 300°F.

**Loctite® QuickStix™ 668™ Retaining Compound**  
Bonds non-threaded cylindrical assemblies with gaps to 0.005". High temperature to 400°F.

**Loctite® QuickStix™ C5-A® Copper Anti-Seize**  
Protects metal parts to 1800°F. Prevents rust, corrosion, seizing; eases disassembly. Fine or coarse threads.

**Loctite® QuickStix™ Silver Grade Anti-Seize**  
Protects metal parts to 1600°F. Prevents rust, corrosion, seizing; eases disassembly. Fine or coarse threads.

**Loctite® QuickStix™ Heavy Duty Anti-Seize**  
Protects metal parts, including stainless steel and aluminum to 2400°F. Metal-free.

**Loctite® QuickStix™ 7088™ Primer**  
Speeds the cure of threadlockers, thread sealants, retaining compounds, and anaerobic gasket products. Ensures proper cure on inactive metals.

**DON'T FORGET!**

ITEM#	SIZE	QUANTITY
37087	19 gm	
37686	19 gm	
37127	19 gm	
37152	18 gm	
39156	19 gm	
39148	19 gm	
37229	20 gm	
37230	20 gm	
41205	20 gm	
1069258	20 gm	

**QuickStix™**  
Portable. Convenient. Clean.



**CHOOSE THE LOCTITE® QUICKSTIX™ THAT ARE RIGHT FOR YOU!**

**FREE HOLSTER WITH EVERY 5 PRODUCTS YOU PURCHASE**