

LOCTITE®

The Flexible Way to Seal and Bond.

LOCTITE® ELASTOMERIC ADHESIVES AND SEALANTS WITH FLEXTEC® TECHNOLOGY



No Primer Required

ALL-WEATHER • ALL-PURPOSE • ALL-MATERIAL

- UV and weather resistant
- Easy extrusion even at 40°F / 5°C
- Insulates against vibration and sound
- Fills gaps
- Seal and bond at the same time
- High initial tack and short curing time
- Replace rivets and mechanical fasteners
- Paintable
- Non-staining
- Adheres to wet surfaces
- Adheres to wide range of substrates (plastic, metal, marble, glass)

1.800.LOCTITE (562-8483)

1.800.263.5043 (Canada)

www.henkelna.com/mroflextec

Innovative Technology



Flextec® Technology indicates the use of Henkel's proprietary materials that generate outstanding handling and performance characteristics in adhesives and sealants. These non-silicone materials are designed for primerless adhesion, speed, and durability in all elastomeric applications.



Excellence is our Passion



Excellence is our Passion



Loctite® 5510™ Adhesive/Sealant

- No dirt pick-up
- Noncorrosive
- High initial tack
- Paintable
- Primerless adhesion
- Fast 24-hour cure
- Excellent UV resistance
- Bonds multiple substrates
- High and flexible final strength
- Easy gunning, even at low temperatures
- 100% solids – no isocyanates, solvents, or harmful by-products



New Part #	Old Part #	Pkg. Size*	Color
1562042	1073344	300 ml cartridge	White
1567697	1194277	50 lb. pail	White
1578972	1197862	250 kg drum	White
1562040	1073349**	300 ml cartridge	Clear
1567698	1197372**	40 lb. pail	Clear
1578971	1210844**	190 kg drum	Clear
1560557	1073347	300 ml cartridge	Black
1567663	1197374	50 lb. pail	Black
1579002	1210842	250 kg drum	Black
1562044	1073346	300 ml cartridge	Grey
1567506	1194276	50 lb. pail	Grey
1579070	1210841	250 kg drum	Grey

*Pails and drums available as made-to-order

**Previously called 5570 Clear

Loctite® 5570™ Adhesive

- Adheres to a wide range of substrates – metals, glass, nylon, ABS, PVC
- Replaces rivets and mechanical fasteners
- Short tack-free and curing time
- Vibration and sound damping
- High initial tack



New Part #	Old Part #	Pkg. Size*	Color
1565679***	1073348	300 ml cartridge	White
1567505***	1197375	50 lb. pail	White
1578969***	1210843	250 kg drum	White

*Pails and drums available as made-to-order

***Available September 2012

Dispensing Equipment Available

Loctite® 300 ml Heavy Duty Manual Cartridge Applicator

Item No. 1093940
 Dimensions: 14.5" L x 2.25" W
 Weight: 2.25 lbs.



Loctite® 300 ml Pneumatic Cartridge Dispenser

Item No. 1294304
 Dimensions: 8" H x 13.5" L x 1.5" D
 Weight: 18 lbs. (800 g)



APPLICATIONS

- General assembly
- Seal expansion joints
- Seal precast panels
- Seal air or water penetration joints
- Bond trim and molding
- Bond roof or side panels to tubular frames
- Seal doors, windows and skylights
- Seal wall penetrations
- Bond flooring to subfloor or metal frames
- Seal siding, roofing and gutters

INDUSTRIES

- Appliance
- HVAC
- Signage/Displays
- General maintenance
- Specialty vehicles
- Agricultural vehicles
- Trailers
- Buses
- Recreational vehicles
- Manufactured housing
- Metallic or wooden construction

Henkel Corporation
 Engineering Adhesives
 One Henkel Way
 Rocky Hill, CT 06067

Henkel Canada Corporation
 2515 Meadowpine Blvd.
 Mississauga, ON L5N 6C3

www.loctite.com
 www.henkelna.com/industrial

1.800.LOCTITE (562-8483)
 1.800.263.5043 (Canada) • www.henkelna.com/mroflextec